

IN THE CLAIMS:

1. **(Currently amended)** A turning opening or closing member supporting structure of a helmet, ~~i.e. a member to be opened or closed under its turning action such as a chin ventilation or a shield,~~ wherein

there is provided an operating mechanism for the turning opening or closing member over a helmet and the turning opening or closing member;

said operating mechanism has a plurality of arc parts for use in controlling a turning action of the turning opening or closing member at any one of either the helmet or the turning opening or closing member;

said arc parts are constituted such that a plurality of more than two arcs having each of different centers of arcs are cooperatively arranged in an integral manner, at least one of the arcs has a center of arc outside the operating mechanism, each of the arc centers including the arc center is coaxial with a center of turning of the turning opening or closing member during its opening or closing operation, and the turning opening or closing member is turned along an orbit of each of the arcs; and thereby

the turning opening or closing member is turned along the orbit of each of said arcs while said center of turning is being switched during its opening or closing operation.

2. **(Currently amended)** A turning opening or closing member supporting structure, wherein

the turning opening or closing member is a chin-ventilation;

an operating mechanism for the turning opening or closing member provided over a helmet and the turning opening or closing member is provided with an arc part (U) at any one of the helmet and the turning opening or closing member, with a first guide shaft (S1) and a second guide shaft (S2) slidably engaged to the arc part (U) at the other of the helmet and the turning opening or closing member, a turning of the turning opening or closing member is cooperatively controlled by ~~these~~ the arc parts part (U) and the two guide shafts;

as said arc ~~parts part~~ part (U) , a first engaging part (U1) with an arc shape having a center of arc outside the operating mechanism, a second engaging part (U2) with an arc shape having a center of arc inside the operating mechanism and a third engaging part (U3) with an arc shape having a center of arc common to that of said first engaging part (U1) are integrally and cooperatively arranged;

each of the centers of arc is coaxial with the center of turning of the turning opening or closing member and the turning opening or closing member is turned along an orbit of the arc of each of the engaging parts; thereby

at the beginning of opening operation of the turning opening or closing member, the turning opening or closing member is guided around the center of turning of ~~the a~~ a first central point (P1) which is a common arc center held by ~~both the first and third~~ the first and third engaging parts under a cooperation of the first guide shaft (S1), the first engaging part (U1), the second guide shaft (S2) and the third engaging part (U3);

when the first guide shaft (S1) reaches a connecting point between the first engaging part (U1) and the second engaging part (U2) during the opening operation, the center of the second guide shaft (S2) reaches a second central point (P2) of the center of arc held by the second engaging part (U2) and at the same time the center of turning of the turning opening or closing member is switched from said first central point (P1) to the second central point (P2) and it is turned around the second guide shaft (S2).

3. **(Currently amended)** A turning opening or closing member supporting structure,

wherein

the turning opening or closing member is a shield;

an operating mechanism for the turning opening or closing member provided over a helmet and the turning opening or closing member is provided with an arc part (U') at any one of the helmet and the turning opening or closing member, with a first guide shaft (S'1) and a second guide shaft (S'2) slidably engaged to the arc part (U') at the other of the helmet and the turning opening or closing member, a turning of the turning opening or closing member is cooperatively controlled by ~~these~~ the ~~arc parts-part~~ arc part and the two guide shafts;

as said ~~arc parts-part~~ arc part (U'), a first engaging part (U'1) with an arc shape having a center of arc outside the operating mechanism, a second engaging part (U'2) with an arc shape having a center of arc inside the operating mechanism are integrally and cooperatively

arranged, each of the centers of arc is coaxial with the center of turning of the turning opening or closing member and the turning opening or closing member is turned along an orbit of the arc of each of the engaging parts; thereby

at the beginning of opening operation of the turning opening or closing member, it is turned around the center of turning of the first central point (P'1) which is the center of arc held by the first engaging part (U'1) under a cooperation of the first guide shaft (S'1) , the second guide shaft (S'2) and the first engaging part (U'1);

when the first guide shaft (S'1) reaches a connecting point between the first engaging part (U'1) and the second engaging part (U'2) during the opening operation, the center of the second guide shaft (S'2) reaches a second central point (P'2) of the center of arc held by the second engaging part (U'2) and at the same time the center of turning of the turning opening or closing member is switched from said first central point (P'1) to the second central point (P'2) and it is turned around the second guide shaft (S'2).

4. **(Currently amended)** A turning opening or closing member supporting structure according to claim 2, wherein

the first engaging part (U1), the second engaging part (U2) and the third engaging part (U3) are of a grooved shape;

the second engaging part (U2) and the third engaging part (U3) of the grooved shape are provided with a step difference, and each

of the shafts is not displaced ~~to the other~~ from one engaging part to another engaging part also at a crossing part of both engaging parts.

5. **(Currently amended)** A turning or closing member supporting structure according to claim 3, wherein

the first engaging part (U'1) and the second engaging part (U'2) are of a grooved shape; and the first engaging part (U'1) and the second engaging part (U'2) of the grooved shape are provided with a step difference, and each of the shafts is not displaced ~~to the other~~ from one engaging part to another engaging part also at a crossing part of both engaging parts.